

INTRODUCTION

This maintenance schedule given below describes the maintenance requirements for the **Daytona 955i** and **Speed Triple 955i** (from 2002 model year).

WARNING: The importance of good maintenance cannot be overestimated. The tasks described will help to ensure the safe and reliable operation of your Triumph motorcycle. Never attempt to cut costs by neglecting the maintenance requirements of your machine as this will result in the premature failure of the component(s) concerned and may lead to an unsafe riding condition and an accident.

Scheduled Maintenance Chart

s	cheduled Maint	enance Ch	art								
Operation Description	Odometer Reading in Miles (Kms) or time period, whichever comes first.										
	Every	500	6000	12000	18000	24000	30000				
		(800) 1month	(10000) 1 year	(20000) 2 years	(30000) 3 years	(40000) 4 years	(50000) 5 years				
Engine oil cooler - check for leaks	-	•	•	•	•	•	•				
Engine oil - renew	-	•	•	•	•	•	•				
Engine oil filter - renew	-	•	•	•	•	•	•				
Valve clearances - check/adjust	-			•		•					
Cam chain wear - check	-					•					
Air cleaner - renew	-			•		•					
Engine ECM - check for stored DTCs	-	•	•	•	•	•	•				
Spark plugs - check	-		•	•		•	•				
Spark plugs - renew	-				•						
Throttle bodies - balance	-			•		•					
Throttle cable - check/adjust	Day	•	•	•	•	•	•				
Cooling system - check for leaks	Day	•	•	•	•	•	•				
Coolant level - check/adjust	Day	•	•	•	•	•	•				
Coolant - renew		Every 2 Years									
Fuel system - check for leaks	Day	•	•	•	•	•	•				
Lights, instrument & electrical systems - check	Day	•	•	•	•	•	•				
Fuel Filter - renew	-			•		•					
Steering - check for free operation	Day	•	•	•	•	•	•				
Headstock bearing - check/adjust	-			•		•					
Headstock bearing - lubricate	-			•		•					
Forks - check for leaks/smooth operation	Day	•	•	•	•	•	•				
Fork oil - renew	-			•		•					
Brake fluid levels - check	Day	•	•	•	•	•	•				
Brake fluid - renew		Every 2 years									
Brake hoses - renew		Every 4 years									
Brake pads - check wear levels	Day	•	•	•	•	•	•				
Brake master cylinder – renew seals		Every 4 years									
Brake calipers - renew seals		Every 4 years									



Operation Description	Odometer Reading in Miles (Kms) or time period, whichever comes first.										
	Every	500	6000	12000	18000	24000	30000				
		(800)	(10000)	(20000)	(30000)	(40000)	(50000)				
		1month	1 year	2 years	3 years	4 years	5 years				
Drive chain - lubricate		Every 200 miles (300 kms)									
Drive chain - wear check	Every 500 miles (800 kms)										
Drive chain slack - check/adjust	Day	•	•	•	•	•	•				
Drive chain rubbing strip - check	-		•	•	•	•	•				
Rear suspension - lubricate		3 years/18000 miles (30000 kms)									
Rear wheel bearing - lubricate (single sided swing arm only)				•		•					
Fasteners - inspect visually for security	Day	•	•	•	•	•	•				
Wheels - inspect for damage	Day	•	•	•	•	•	•				
Tyre wear/tyre damage - check	Day	•	•	•	•	•	•				
Tyre pressures - check/adjust	Day	•	•	•	•	•	•				
Clutch cable - check/adjust	Day	•	•	•	•	•	•				
Secondary air injection system - clean and reset				•			•				
Fuel/evaporative* hoses - renew		Every 4 years									

^{*} Evaporative hoses on California models only