

INTRODUCTION

This maintenance schedule given below describes the maintenance requirements for the **Sprint ST** and **Sprint RS** models from 2002 model year.

WARNING: The importance of good maintenance cannot be overestimated. The tasks described will help to ensure the safe and reliable operation of your Triumph motorcycle. Never attempt to cut costs by neglecting the maintenance requirements of your machine as this will result in the premature failure of the component(s) concerned and may lead to an unsafe riding condition and an accident.

Scheduled Maintenance Chart

Scheduled Maintenance Chart											
Operation Description	Odometer Reading in Miles (Kms) or time period, whichever comes first.										
	Every	500	6000	12000	18000	24000	30000				
		(800)	(10000)	(20000)	(30000)	(40000)	(50000)				
		1month	1 year	2 years	3 years	4 years	5 years				
Engine oil cooler - check for leaks	-	•	•	•	•	•	•				
Engine oil - renew	-	•	•	•	•	•	•				
Engine oil filter - renew	Day	•	•	•	•	•	•				
Valve clearances - check/adjust	-			•		•					
Cam chain wear - check	-					•					
Air cleaner - renew	-			•		•					
Engine ECM - check for stored DTCs	-	•	•	•	•	•	•				
Spark plugs - check	-		•	•		•	•				
Spark plugs - renew	-				•						
Throttle bodies - balance	-			•		•					
Throttle cable - check/adjust	Day	•	•	•	•	•	•				
Cooling system - check for leaks	Day	•	•	•	•	•	•				
Coolant level - check/adjust	Day	•	•	•	•	•	•				
Coolant - renew	Every 2 Years										
Fuel system - check for leaks	Day	•	•	•	•	•	•				
Lights, instruments & electrical systems - check	Day	•	•	•	•	•	•				
Fuel Filter - renew	-			•		•					
Steering - check for free operation	Day	•	•	•	•	•	•				
Headstock bearing - check/adjust	-			•		•					
Headstock bearing - lubricate	-			•		•					
Forks - check for leaks/smooth operation	Day	•	•	•	•	•	•				
Fork oil - renew	-			•		•					
Brake fluid levels - check	Day	•	•	•	•	•	•				
Brake fluid - renew	Every 2 years										
Brake hoses - renew	Every 4 years										



Scheduled Maintenance Chart (continued)										
Operation Description	Odometer Reading in Miles (Kms) or time period, whichever comes first.									
	Every	500	6000	12000	18000	24000	30000			
		(800)	(10000)	(20000)	(30000)	(40000)	(50000)			
		1month	1 year	2 years	3 years	4 years	5 years			
Brake pads - check wear levels	Day	•	•	•	•	•	•			
Brake master cylinder - renew seals	Every 4 years									
Brake calipers - renew seals	Every 4 years									
Drive chain - lubricate	Every 200 miles (300 kms)									
Drive chain - wear check	Every 500 miles (800 kms)									
Drive chain slack - check/adjust	Day	•	•	•	•	•	•			
Drive chain rubbing strip - check	=		•	•	•	•	•			
Rear suspension - lubricate	3 years/18000 miles (30000 kms)									
Rear wheel bearing - lubricate (single sided swing arm only)				•		•				
Fasteners - inspect visually for security	Day	•	•	•	•	•	•			
Wheels - inspect for damage	Day	•	•	•	•	•	•			
Tyre wear/tyre damage - check	Day	•	•	•	•	•	•			
Tyre pressures - check/adjust	Day	•	•	•	•	•	•			
Clutch cable - check/adjust	Day	•	•	•	•	•	•			
Fuel and evaporative hoses* - renew	Every 4 years									
Secondary air injection system - clean and reset	-			•		•				

^{*} Evaporative hoses on California models only